



GRUNDFOS 

CR 10

ردیف	مدل	ولتاژ و فاز	RPM	توان موتور P _r HP	توان موتور P _r KW	شدت جریان	حداکثر هد (متر)	حداقل هد (متر)	حداکثر دبی (متر مکعب در ساعت)	قطر دهانه ورودی mm	قطر دهانه خروجی mm
1	CR 10-4	3×380-415Y	2910	1/5	2	3/15	40/91	22/32	5-13.1	1½"	1½"
2	CR 10-5	3×380-415Y	2910	2/2	3	4/45	51/36	28/83	5-13.1	1½"	1½"
3	CR 10-6	3×380-415Y	2910	2/2	3	4/45	61/52	34/83	5-13.1	1½"	1½"
4	CR 10-7	3×380-415D	2920	3	4	6/3	71/92	40	5-13.1	1½"	1½"
5	CR 10-8	3×380-415D	2920	3	4	6/3	81/99	46/44	5-13.1	1½"	1½"
6	CR 10-9	3×380-415D	2920	3	4	6/3	92	52/09	5-13.1	1½"	1½"
7	CR 10-10	3×380-415D	2940	4	5/5	7/9	102/8	59/76	5-13.1	1½"	1½"
8	CR 10-12	3×380-415D	2940	4	5/5	7/9	123/3	70	5-13.1	1½"	1½"
9	CR 10-14	3×380-415D	2940	5/5	7/5	11	144	83/21	5-13.1	1½"	1½"
10	CR 10-16	3×380-415D	2940	5/5	7/5	11	164/3	93/77	5-13.1	1½"	1½"
11	CR 10-18	3×380-415D	2920	7/5	10	14.4-14	185/5	106/2	5-13.1	1½"	1½"
12	CR 10-20	3×380-415D	2920	7/5	10	14.4-14	206	120	5-13.1	1½"	1½"
13	CR 10-22	3×380-415D	2920	7/5	10	14.4-14	226/4	129/6	5-13.1	1½"	1½"

۰۲۱-۳۶۶۱۳۴۴۰

۰۲۱-۳۳۹۰۵۴۳۵