



CR 20

GRUNDFOS 

ردیف	مدل	ولتاژ و فاز	RPM	توان موتور P _۲ KW	توان موتور P _۲ HP	شدت جریان	حداکثر هد (متر)	حداقل هد (متر)	حداکثر دبی (متر مکعب در ساعت)	قطر دهانه ورودی mm	قطر دهانه خروجی mm
1	CR 20-4	3×380-415D	2940	5/5	7/5	11	58/8	28/89	10.7-29.4	2"	2"
2	CR 20-5	3×380-415D	2940	5/5	7/5	11	73/35	35	10.7-29.4	2"	2"
3	CR 20-6	3×380-415D	2920	7/5	10	14.4-14	88/94	45	10.7-29.4	2"	2"
4	CR 20-7	3×380-415D	2920	7/5	10	14.4-14	104	52/47	10.7-29.4	2"	2"
5	CR 20-8	3×380-415D	2950	11	15	20.8-19.8	120	60	10.8-29.4	2"	2"
6	CR 20-10	3×380-415D	2950	11	15	20.8-19.8	148/9	78/22	10.8-29.4	2"	2"
7	CR 20-12	3×380-415D	2950	15	20	28-26	178/7	92	10.8-29.4	2"	2"
8	CR 20-14	3×380-415D	2950	15	20	28-26	208	107/6	10.8-29.4	2"	2"
9	CR 20-17	3×380-415D	2950	18/5	25	34.5-32.5	251/6	130/8	10.8-29.4	2"	2"

۰۲۱-۳۶۶۱۳۴۴۰

۰۲۱-۳۳۹۰۵۴۳۵