



CR 5

GRUNDFOS 

ردیف	مدل	ولتاژ و فاز	RPM	توان موتور P _r KW	توان موتور P _r HP	شدت جریان	حداکثر هد (متر)	حداقل هد (متر)	حداکثر دبی (متر مکعب در ساعت)	قطر دهانه ورودی mm	قطر دهانه خروجی mm
2	CR 5-7	3×380-415Y	2870	1/1	1/5	2/5	48/76	20/99	2.5-8.43	1"/1¼"	1"/1¼"
3	CR 5-8	3×380-415Y	2870	1/1	1/5	2/5	55/43	23/54	2.5-8.35	1"/1¼"	1"/1¼"
4	CR 5-9	3×380-415Y	2910	1/5	2	3/15	63	27/37	2.5-8.55	1"/1¼"	1"/1¼"
5	CR 5-10	3×380-415Y	2910	1/5	2	3/15	70	30	2.5-8.53	1"/1¼"	1"/1¼"
6	CR 5-11	3×380-415Y	2910	2/2	3	4/45	77/17	34/25	2.5-8.58	1"/1¼"	1"/1¼"
7	CR 5-12	3×380-415Y	2910	2/2	3	4/45	83/91	37/67	2.5-8.56	1"/1¼"	1"/1¼"
8	CR 5-13	3×380-415Y	2910	2/2	3	4/45	90/88	40	2.5-8.57	1"/1¼"	1"/1¼"
9	CR 5-14	3×380-415Y	2910	2/2	3	4/45	97/64	44/68	2.5-8.49	1"/1¼"	1"/1¼"
10	CR 5-15	3×380-415Y	2910	2/2	3	4/45	104/4	47/95	2.5-8.47	1"/1¼"	1"/1¼"
11	CR 5-16	3×380-415Y	2910	2/2	3	4/45	111/4	50	2.5-8.52	1"/1¼"	1"/1¼"
12	CR 5-18	3×380-415D	2920	3	4	6/3	125/8	57/91	2.5-8.54	1"/1¼"	1"/1¼"
13	CR 5-20	3×380-415D	2920	3	4	6/3	140	64/63	2.5-8.49	1"/1¼"	1"/1¼"
14	CR 5-22	3×380-415D	2940	4	5/5	7/9	154/4	71/88	2.5-8.61	1"/1¼"	1"/1¼"
15	CR 5-24	3×380-415D	2940	4	5/5	7/9	168/1	80	2.5-8.61	1"/1¼"	1"/1¼"
16	CR 5-26	3×380-415D	2940	4	5/5	7/9	182/3	85/46	2.5-8.56	1"/1¼"	1"/1¼"
17	CR 5-29	3×380-415D	2940	4	5/5	7/9	203	94/63	2.5-8.56	1"/1¼"	1"/1¼"
18	CR 5-32	3×380-415D	2940	5/5	7/5	11	224/7	106/8	2.5-8.53	1"/1¼"	1"/1¼"

۰۲۱-۳۶۶۱۳۴۴۰

۰۲۱-۳۳۹۰۵۴۳۵